



Interrow Cultivator - and grain drill



agromek 
STARS 2022

CMN maskintec A/S
M9750

Nyhedsværdi



C tand for præcis redensning
Den stive C tand giver en mere stabil styring mellem afgraderækkerne. C tandens lette justering af aggressiviteten, giver mulighed for hurtig justering i forhold til afgrødens størrelse.

agromek 
STARS 2022

CMN maskintec A/S
M9750

Nyhedsværdi



Intelligent dybde styring af radrensesektion
Radrensningens præcision øges markant ved montering af ultralyds sensorer der løbende justerer skærdybden på sektionens niveau. Automatisk dybdestyring af radrensesektioner er noget helt nyt og unikt.

CMN C-tooth ★★ news for Agromek 2022

As something completely new, CMN C tooth has been developed for season 2023. The tooth is very special in design, it is adjustable in suspension at the same time it is rigid sideways. As something completely new, you can also set the cutting angle, which provides great flexibility when cleaning large and small plants.



CMN Interrow Cleaner ★★ Agromek new 2022 - can now offer the patent-pending automatic depth control system.

The system is sensor-based, it works electrically and hydraulically and is operated by a screen from the tractor. With this system, soil coverage of plants is avoided when laying soil in between plants, the system will always ensure the correct working depth of the schar.

★★★ Agromek Europa nyhed 2022



You can also advantageously mount the CMN FS 1000 or FS 1500 front tank, you can then sow your cereal or protein crops with the same CMN hoe. This way you can save yourself the investment in a new seed drill.

It is now possible to mount all machines with auto control unit or front mounting frame, which means that the machine is easier to control - even at high speed.

If cover crops are to be sown, we can mount the machine with a CMN pneumatic seeder.

The horizontal goosefoot causes a significantly smaller incentive for new weed seeds to germinate after cleaning, because full cutting can be achieved.

When using after harrows, a control of the weeds between the plants is ensured.

The individual parallelograms can be placed stepless on the mainframe in relation to the selected row spacing.

If CMN interrow cleaner is used for grains at 25 cm. row spacing 1 or 3 rows of grain are divided for each parallelogram.

For the intersection between the rows, wide share can be used.



Steering Frame



The CMN Steering Frame is designed to mount between the tractor and the implement.

The steering frame can be controlled by a camera – the tractor's GPS or directly from the tractor's hydraulic outlet.

The CMN steering frame is standard cat. 3 lift and this fits standard on the implement.

The frame has 25 cm side shift to each side





Interrow Cultivator

Specifications and options.

- ✓ Working width: 3-4-6-9 m.
- ✓ Camera auto steering
- ✓ Side shift frame
- ✓ C-tooth ★ ★ Agromek news 2022
- ✓ Automatic depth regulation ★ ★ ★ Agromek news 2022
- ✓ Electric / hydraulic section lift
- ✓ Front mount
- ✓ Rear mount
- ✓ Row spacing from 15 cm.
- ✓ Parallel suspended sections
- ✓ Screen plates
- ✓ Roller inserts
- ✓ Spring-loaded finger harrows



More informations



AC Hoppesvej 5
Tlf +45 97 87 20 00
www.cmn.dk

DK 7790 Thyholm
mail@cmn.dk



Dealer